
	The major to a											
POLE TYPE	POLE DATA					BASE PLATE DATA					CIDH PILE DATA	
	HEIGHT "h"	Min OD		THICKNESS BOTTOM SEGMENT	Min THICKNESS	Dia	THICKNESS	ANCHOR BOLT SIZE		BC = BOLT CIRCLE	"D"	n ₁ n
		BASE	TOP	(Min 25' LONG)	UPPER SEGMENT(S)	DIG	IHICKNE 33	TOTAL	"d"	DO - BOLT CINCLE	"	
HM CAMERA POLE 50	50′	18"	10%"	0.3125"	0.1875"	32"	2"	12	21/4"	25"	3′-6"	13'-0"
HM CAMERA POLE 60	60′		91/2"									
HM CAMERA POLE 70	70′	22"	12"			36"	3"			29"	4'-0"	14'-0"
HM CAMERA POLE 80	80′	22"	115/8"	0.375"	0.25"	39"			3"	30"	4'-6"	14-0
HM CAMERA POLE 90	90′	25"	171/8"			46"				37"	6'-0"	15'-0"



DETAIL A

NOTES:

DETAIL B

- Pole details shall suit the lowering device and this foundation plan. Pole details shall be submitted to the Engineer for approval.
- Access opening shall be located on the downstream side of traffic unless otherwise determined by the Engineer.
- 3. Foundation design is based on a 3-second wind gust of 100 mph.
- 4. For central void and drain holes in mortar, see Standard Plan ES-6B detail N.
- 5. For wind loading see Revised Standard Plan RSP ES-7M.
- 6. Materials (Structural Steel):

fy = 55,000 psi (tapered steel tube) fy = 50,000 psi (unless otherwise noted)

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

ELECTRICAL SYSTEMS (HIGH MAST CAMERA POLE 50' TO 90')

NO SCALE

RSP ES-16C DATED OCTOBER 19, 2018 SUPERSEDES STANDARD PLAN ES-16C DATED MAY 31, 2018 - PAGE 554 OF THE STANDARD PLANS BOOK DATED 2018.

REVISED STANDARD PLAN RSP ES-16C

ES-7N Det A


POLE

ELEVATION A

"D"

MEDIAN LOCATION

ELEVATION C



TOP VIEW
DETAIL D

DETAIL C

VISED

STANDARD

2

P

RSP

ES-16C